



# HD 150 TT

HD 150 TT - Rubber wheeled roller



- ▶ Driver seat including steering wheel and instrument panel can be swivelled and rotated
- ▶ Ergonomic driver seat with 2 multifunction drive levers
- ▶ Optimum visibility, view of tyre's outer edges
- ▶ Diesel engine with high power and low sound level
- ▶ Precise adjustment of water sprinkler system



## HD 150 TT

### Weights

Operating weight with ROPS	kg	14075
Operating weight with cab	kg	14340
Operating weight, max.	kg	14870
Axle load, front/rear	kg	7235/7105
Load per tyre, front/rear	kg	1808,75/1776,25

### Machine dimensions

Max. working width	mm	1910
Ground clearance, left/right	mm	785/785
Ground clearance, centre	mm	340
Turning radius, inside	mm	4020
Size of tyres, front/rear		11.00-R20/11.00-R20

### Diesel engine

Manufacturer	DEUTZ	
Version	TCD 2012 L04 2V	
Number of cylinders	4	
Power rat. ISO 14396, kW/PS/rpm	85,0/115,6/2300	
Power rating SAE J1349, kW/HP/rpm	85,0/113,9/2300	
Emissions standard EU/USA	III A / Tier 3	
Fuel tank, capacity	L	185

### Drive

Hydrostatic drive, front/rear		Wheel motor/Wheel motor
Speed, working gear	km/h	0-6,5
Speed, transportation gear	km/h	0-13,0
Climbing ability	%	40

### Steering

Steering, type		Articulated steering
Steering, actuation		hydrostatic, steering wheel
Steering angle +/-	°	39
Oscillation angle +/-	°	2,5

### Sprinkler system

Water sprinkler, type		Pressure
Actuation, water sprinkler		interval/manual
Water tank, capacity	L	900

### Equipment

Spring-mounted tiltable driver stand, 1 comfort seat, can be swivelled and rotated, 2 multifunction drive levers, Operating hours counter, Fuel level, Indicator lights and emergency stop switch, 2 spotlights, rear, Battery main switch, Triple oil filtering, Water level indicator

### Optional equipment

ROPS panoramic cab, Dust-free ventilation, Sun visor, Interior lighting, Front and rear windscreen wiper, Interior rearview mirror, Rotating beacon, ROPS/FOPS, Safety belt, Speedometer, Noise isolation, Sun roof, Radio, Special colour, Back-up alarm, Asphalt thermometer, Tyre heating, Thermal aprons, Automatic tyre level system: from driver seat, can use a powerful compressor to regulate inflation pressure quickly (from 1.5–8 bar) while driving

# HD 150 TT

HD 150 TT - Rubber wheeled roller



<b>Total length</b>	<b>L</b>	<b>4550</b>
<b>Width</b>	<b>B</b>	<b>1810</b>
<b>Total height</b>	<b>H</b>	<b>3065</b>
<b>Wheel base</b>	<b>A</b>	<b>3410</b>
<b>Width over tyres</b>	<b>Y</b>	<b>1680/1680</b>
<b>Diameter of tyres</b>	<b>R</b>	<b>1070/1070</b>
<b>Height loading, min.</b>	<b>HI</b>	<b>2350</b>

